



DIFFERENTIAL



#2084

LIMITED SLIP LUBRICANT

Use every 30,000 miles or MFG recommended schedule service
Reduces noise and vibration and clutch plate slippage.



#2076

SAE 75W-90 SYNTHETIC DIFFERENTIAL FLUID

Use every 30,000 miles or MFG recommended schedule service

A multi-purpose lubricant to provide excellent thermal and oxidation stability. Extends lubricant life while its high viscosity index and low pour point provide safe operation over a wide temperature range. Suitable for drain and refill use in limited slip differentials. It exceeds performance requirements of today's rear axles, transmissions and differentials in all types of over-the-road, off-road automotive and racing applications (API GL-5).



#2080

SAE 75W-140 SYNTHETIC DIFFERENTIAL FLUID

Use every 30,000 miles or MFG recommended schedule service

A high performance gearboxes and differentials oil. This product is a multi-purpose lubricant to provide excellent thermal and oxidation stability. Extends lubricant life while its high viscosity index and low pour point provide safe operation over a wide temperature range. Suitable for drain and refill use in limited slip differentials.

It exceeds performance requirements of today's rear axles transmissions and differentials in all types of over-the-road, off-road automotive and racing applications (API GL-5).

PROTECTING YOUR CAR WITH PROTECH
PRODUCTS WILL IMPROVE PERFORMANCE,
LONGEVITY AND IS COST EFFECTIVE