


## #2032 TRANSMISSION CONDITIONER

Use every 30,000 miles or MFG recommended schedule service

Designed with a special additive package that smooths gear changing and removes varnish deposits that cause slippage in the transmission. It contains an anti-friction formula for front or rear wheel drive transmissions to prevent metal wear, and contains active detergents to clean oil oxidation deposits. It also revitalizes seals and o-rings to prevent leaks.

Remove 11 oz. of ATF from the transmission and then add the **entire content**.



## #2036 TRANSMISSION CONDITIONER WITH SHUDDER CONTROL

Use every 30,000 miles or MFG recommended schedule service

Utilizes advanced additive technology. Proven to be compatible with all ATF's and transmission materials.

Eliminates shudder in automatic transmissions and ensures smooth shifting.



## #2072 75X85 SYNTHETIC TRANSAXLE FLUID

Use every 30,000 miles or MFG recommended schedule service

Formulated for use in all transfer case and transmission applications specifying ATF or GL-1 thru GL-4 gear oils.

In addition, this fluid is recommended for use in the following OEM specific applications.

GM P/N 12345349

Ford P/N D80Z19C547A and ESRV 19C547

Chrysler P/N 4773167

Mercedes-Benz P/N 900260315

# TRANSMISSION

DO  
YOU **KNOW?**